

生コン工場 規格		W/C	1	2	3	4	5	6	7	8	9	10	11	12
			更水生コン(株)	信州生コン(株) 更埴工場	信州生コン(株) 豊野工場	信州生コン(株) 大橋工場	㈱宮下 宮下生コン工場	さくら生コン(株) 須坂工場	西山生コン(株)	㈱ホリウチ 堀内生コン工場	長野生コン(株)	宮島産業(株) 宮島生コン工場	㈱本久 長野生コン工場	(有)轟商会
1	18-8-25-BB	60%以下												
		65%以下	●		●	●	●	●	●	●	●	●	●	●
		60%以下												
2	18-8-40-BB	65%以下	●		●	●	●	●	●	●	●	●	●	●
		55%以下												
3	21-5-40-BB	60%以下	●		●	●		●	●			●	●	
		55%以下												
4	21-8-25-BB	60%以下	●	●	●	●	●	●	●	●	●	●	●	●
		65%以下												
		55%以下												
5	21-8-40-BB	60%以下	●	●	●	●	●	●	●	●	●	●	●	●
		65%以下												
		55%以下												
6	21-12-40-BB	55%以下									●			
		60%以下	●											
7	24-5-40-BB	55%以下								●				
		50%以下												
8	24-8-25-BB	55%以下	●	●	●	●	●	●	●	●	●	●	●	●
		60%以下												
		50%以下												
9	24-8-40-BB	55%以下	●	●	●	●	●	●	●	●	●		●	●
		60%以下												
		50%以下												
10	24-12-25-BB	50%以下		●	●		●	●			●		●	
		55%以下												
11	24-12-40-BB	50%以下		●	●		●	●			●		●	
		55%以下												
		45%以下												
12	30-8-25-BB	50%以下			●	●								●
		55%以下	●											
		55%以下												
13	30-12-25-BB	55%以下			●	●								●
		45%以下												
		45%以下												
14	曲-4.5-2.5-40-BB	45%以下					●					●		
		315kg以上												
15	曲-4.5-6.5-40-BB	45%以下					●					●		
		315kg以上												
16	18-8-25-N	65%以下	●		●	●		●		●		●		●
		65%以下	●		●	●		●		●		●		●
17	18-8-40-N	60%以下	●		●	●		●		●		●		●
		65%以下	●		●	●		●		●		●		●
18	21-5-40-N	60%以下	●		●	●		●		●		●		●
		65%以下	●		●	●		●		●		●		●
19	21-8-25-N	60%以下	●		●	●		●		●		●		●
		65%以下	●		●	●		●		●		●		●
20	21-8-40-N	60%以下	●		●	●		●		●		●		●
		65%以下	●		●	●		●		●		●		●
21	24-5-40-N	60%以下	●							●				
		50%以下												
22	24-8-25-N	55%以下	●		●	●		●		●		●		●
		60%以下								●				
		50%以下												
23	24-8-40-N	55%以下	●		●	●		●		●				●
		60%以下								●				
		50%以下												
24	24-12-25-N	55%以下			●	●		●			●			
		55%以下												
25	24-12-40-N	55%以下			●	●		●						
		50%以下												
26	30-8-25-N	50%以下			●	●								●
		55%以下	●											
27	30-12-25-N	50%以下			●	●				●		●		
		55%以下												
		45%以下												
28	曲-4.5-2.5-40-N	315kg以上												
		45%以下												
29	曲-4.5-6.5-40-N	315kg以上										●		
		45%以下												
30	18-8-25-H	60%以下	●		●	●	●	●	●	●	●	●	●	●
		65%以下	●		●	●	●	●	●	●	●	●	●	●
31	18-8-40-H	60%以下	●		●	●	●	●	●	●	●	●	●	●
		65%以下	●		●	●	●	●	●	●	●	●	●	●
32	21-8-25-H	55%以下	●		●	●	●	●	●	●	●	●	●	●
		60%以下	●		●	●	●	●	●	●	●	●	●	●
		65%以下	●		●	●	●	●	●	●	●	●	●	●
33	21-8-40-H	55%以下	●		●	●	●	●	●	●	●	●	●	●
		60%以下	●		●	●	●	●	●	●	●	●	●	●
		65%以下	●		●	●	●	●	●	●	●	●	●	●
34	24-8-25-H	55%以下	●		●	●	●	●	●	●	●	●	●	●
		60%以下	●		●	●	●	●	●	●	●	●	●	●
35	24-8-40-H	50%以下	●		●	●	●	●	●	●	●	●	●	●
		55%以下	●		●	●	●	●	●	●	●	●	●	●
36	24-12-25-H	55%以下	●		●	●	●	●	●	●	●	●	●	●
		55%以下	●		●	●	●	●	●	●	●	●	●	●
37	24-12-40-H	55%以下	●		●	●	●	●	●	●	●	●	●	●
		55%以下	●		●	●	●	●	●	●	●	●	●	●
38	27-8-25-H	50%以下	●									●		
		50%以下	●											
39	30-8-25-H	55%以下	●							●				●
		55%以下	●											
40	30-12-25-H	55%以下									●			
		55%以下												
41	36-8-25-H	55%以下									●			
		55%以下												
42	36-12-25-H	55%以下									●			
		55%以下												
43	40-8-25-H	55%以下									●			
		55%以下												
44	40-12-25-H	55%以下									●			
		55%以下												

(注1)設計単価との整合を図る際には、水セメント比を指定して下さい。

(注2)「捨てコン」はJIS規格外製品であり、判定基準がないので一括承認の対象としません。